

PRICE BID FOR CONSTRUCTION OF OPEN CANAL IN THE SUB-STATION AT THE 400/220/132KV BYRNIHAT SUB-STATION, KILLING

| Sl. No. | Particulars | Nos | Length(m) | Width(m) | Height(m) | Quantity | Unit | Rate (Rs.) | Amount (Rs.) |
|------------------------|--|--------|-----------|------------------|------------|-----------------------------------|------|------------|--------------|
| 1 | A. Construction of catch water/intercepting drain in random rubble masonry in 1:5 cement mortar true to the specified lines, grades, levels and dimension as per the requirement of the specifications Clause 1606.2 A. Earthwork in excavation for structures as per drawing and technical specification By manual means: V. Marshy soil | 1 | 84 | 4.8 | 0.3 | 120.96 | cum | | |
| 2 | Providing brick soling in foundation and under floor with stone/ best quality picked jhama brick, sand packed and laid to level and in panel after preparing the subgrade as directed including all labour and materials and if necessary dewatering, complete (d). Stone soling of thickness 150mm | 2 | 84 | 4.8 | - | 806.40 | sqm | | |
| 3 | B. Plain cement concrete M10 grade (i). Nominal mix 1:3:6 | 1 | 84 | 4.8 | 0.2 | 80.64 | cum | | |
| 4 | C. Stone masonry in cement mortar 1:5 Coursed rubble masonry(1st sort) in cement mortar 1:5 | 2 2 | 84 84 | 0.6 1/2 x 1.2 | 1.2 1.2 | 120.96 120.96 <u>241.92</u> | cum | | |
| 5 | D. Plain cement concrete M15 grade (i). Nominal mix 1:2:4 | 2 | 84 | 0.6 | 0.1 | 10.08 | cum | | |
| 6 | E. Cement plaster 15mm thick 1:4 on stone masonry In cement mortar 1:4 | 2 2 | 84 84 | 1.7 1.2 | - - | 285.60 201.60 <u>487.20</u> | sqm | | |
| Total in Rupees | | | | | | | | | |

